

# Soils

— THE TOUGHEST —  
**PERFORMER**  
« FOR YOUR FIELD »

**26**  
**XTRA**



REINFORCED  
SAFETY FEATURES

HIGH LIFTING  
CAPACITY

POWER PACKED  
ENGINE

REMASTERED  
TRANSMISSION

ADVANCED  
TECH EDGE

FRICTION-LESS  
AERODYNAMICS &  
LED PROJECTION



**COST**  
**EFFICIENT**  
MECHANICAL TRACTORS

MADE OF  
**REAL**  
**STEEL**

STRATEGIC  
COLLABORATION  
WITH  
**YANMAR**

**THE TOUGHEST  
PERFORMER  
FOR YOUR FIELD**

**26  
XTRA**

**SOLIS**



FEATURES	S 26
Model Description	SOLIS-26
<b>ENGINE</b>	
Engine Type	Mitsubishi 3 Cylinder
HP Category	26
No. of Cylinders	3
Aspiration	Natural
Cubic Capacity (cc)	1318
Rated RPM	2700
Air cleaner	Dry
Cold Start	Yes
Max Torque (nm)	76.3@2700
Exhaust	Underhood Downdraft Silencer
<b>TRANSMISSION</b>	
Drive	4WD
Clutch	Single Clutch
Gearbox	6F+2R
Front Axle	4WD
Transmission	Sliding Mesh
<b>SPEED (FORWARD)</b>	
Maximum Speed (Km/Hr)	15.58 @ 2700
Minimum Speed (Km/Hr)	1.07 @ 2700
<b>BRAKES</b>	
Brakes	Oil Immersed Brakes
Type of actuation	Mechanical
Parking Brake	Independent
<b>DIFFERENTIAL LOCK</b>	
Differential lock	Yes, Foot Operated
<b>PTO</b>	
PTO (rpm)	540, 1000
PTO (actuation)	Mechanical
<b>STEERING</b>	
Steering	Power
<b>ELECTRICAL</b>	
Battery	12V, 65Ah
Type of Actuation	12V, 42Amp
Parking Brake	Yes
<b>HYDRAULICS</b>	
3 point linkage	Cat-I
Stay Bars	Anchor Chain
Lifting Capacity	600Kg
Auxiliary hydraulic circuit	1DA/ 1SA
Lift rods	Yes

FEATURES	S 26
Flow(LPM)	14
<b>SAFETY SWITCH</b>	
Clutch Safety Switch	Yes
PTO Safety Switch	Yes
Neutral Safety Switch	Yes
<b>CAPACITY (LTRS)(+/-5%)</b>	
Fuel tank (Lit)	2.7
<b>TURNING RADIUS</b>	
Without Brakes (m)	2.3
<b>TYRE</b>	
Front	6.00-12
Rear	8.30-20
<b>DIMENSION &amp; WEIGHT(+/-5%)</b>	
Weight(kg)	1020
Wheel Base (mm)	1560
Total Length (mm)	2725
Total Width (mm)	1030
Height (mm) Up to ROPS	2153
Min Ground Clearance (mm)	255
Front Track (mm)	894
Rear Track (mm)	825
<b>OTHERS</b>	
Fuel Indicator gauge	Yes
Front Toe Hook	Yes
Front & rear weights with std. Ballast	Front weights-15x2
Trailer Hitch	1. Clevis Hitch 2. Swinging Drawbar (Optional)
<b>ROPS</b>	Yes
<b>OPTIONAL FEATURES</b>	
Tyres	<b>TURF TYRES:</b> Front Tyre - 23x8.50-12 Rear tyre - 33x15.50-16.5  <b>WIDE AGRI TYRES:</b> Front tyre- 7.14 Rear tyre- 8.3X20

\*Since product improvement is a continuous process, specification and details provided are subject to change without prior notice. E&OE. Please correlate with latest updates, accessories shown may not be part of standres product.

**DEALER STAMP**



**YANMAR PHILIPPINES CORPORATION**